

UDFN4 3.0x3.0, 1.30P CASE 517DB **ISSUE A**

DATE 17 SEP 2014

NOTES:

- NOTES:

 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.

 2. CONTROLLING DIMENSION: MILLIMETERS.

 3. DIMENSION & APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.05 AND 0.15 MM FROM THE TERMINAL TIP.

 4. COPLANARITY APPLIES TO THE EXPOSED PADS AS WELL AS THE TERMINALS.

 5. POSITIONAL TOLERANCE APPLIES TO ALL OF THE FXPOSED PADS.
- OF THE EXPOSED PADS.

	MILLIMETERS		
DIM	MIN	MAX	
Α	0.45	0.55	
A1	0.00	0.05	
A3	0.13 REF		
b	0.35	0.45	
D	3.00 BSC		
D2	0.95	1.05	
D3	1.15	1.25	
Е	3.00 BSC		
E2	1.80	1.90	
E3	0.75	0.85	
E4	0.65	0.75	
е	1.30 BSC		
F	0.75 BSC		
F1	0.70 BSC		
G	0.48 BSC		
L	0.35	0.55	

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code

= Assembly Location Α


= Year WW = Work Week = Pb-Free Package


(Note: Microdot may be in either location)


*This information is generic. Please refer to device data sheet for actual part mark-

Pb-Free indicator, "G" or microdot " ■", may or may not be present.


D - A B PIN ONE INDICATOR E 2X \alpha 0.10 0.10 С **TOP VIEW**







RECOMMENDED SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON91435F	Electronic versions are uncontrolle	
STATUS:	ON SEMICONDUCTOR STANDARD	accessed directly from the Document F versions are uncontrolled except w	
NEW STANDARD:		"CONTROLLED COPY" in red.	
DESCRIPTION:	UDFN4 3.0X3.0, 1.30P		PAGE 1 OF 2



DOCUMENT	NUMBER:
98AON91435	F

PAGE 2 OF 2

ICCLIE	DEVICION	DATE
ISSUE	REVISION	DATE
0	RELEASED FOR PRODUCTION. REQ. BY D. TRUHITTE.	15 SEP 2014
Α	CORRECTED GENERIC MARKING DIAGRAM. REQ. BY D. TRUHITTE.	17 SEP 2014

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.