



ON Semiconductor®

FGH60N60SFDTU-F085

600 V, 60 A Field Stop IGBT

Features



- High Current Capability
- Low Saturation Voltage: $V_{CE(sat)} = 2.2 \text{ V}$ @ $I_C = 60 \text{ A}$
- High Input Impedance
- Fast Switching
- RoHS Compliant
- Qualified to Automotive Requirements of AEC-Q101

Applications

- Automotive chargers, Converters, High Voltage Auxiliaries
- Inverters, PFC, UPS

General Description

Using Novel Field Stop IGBT Technology, ON Semiconductor's new series of Field Stop IGBTs offer the optimum performance for Automotive Chargers, Inverter, and other applications where low conduction and switching losses are essential.



Absolute Maximum Ratings

| Symbol | Description | Ratings | Unit |
|-------------|---|-------------|------------------|
| V_{CES} | Collector to Emitter Voltage | 600 | V |
| V_{GES} | Gate to Emitter Voltage | ± 20 | V |
| | Transient Gate-to-Emitter Voltage | ± 30 | |
| I_C | Collector Current @ $T_C = 25^\circ\text{C}$ | 120 | A |
| | Collector Current @ $T_C = 100^\circ\text{C}$ | 60 | A |
| $I_{CM(1)}$ | Pulsed Collector Current @ $T_C = 25^\circ\text{C}$ | 180 | A |
| P_D | Maximum Power Dissipation @ $T_C = 25^\circ\text{C}$ | 378 | W |
| | Maximum Power Dissipation @ $T_C = 100^\circ\text{C}$ | 151 | W |
| T_J | Operating Junction Temperature | -55 to +150 | $^\circ\text{C}$ |
| T_{stg} | Storage Temperature Range | -55 to +150 | $^\circ\text{C}$ |
| T_L | Maximum Lead Temp. for soldering Purposes, 1/8" from case for 5 seconds | 300 | $^\circ\text{C}$ |

Notes:

1: Repetitive test, Pulse width limited by max. junction temperature

Thermal Characteristics

| Symbol | Parameter | Typ. | Unit |
|-------------------------------|---|------|---------------------------|
| $R_{\theta JC}(\text{IGBT})$ | Thermal Resistance, Junction to Case | 0.33 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JC}(\text{Diode})$ | Thermal Resistance, Junction to Case | 1.1 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient | 40 | $^\circ\text{C}/\text{W}$ |

Package Marking and Ordering Information

| Part Number | Top Mark | Package | Packing Method | Reel Size | Tape Width | Quantity |
|--------------------|-------------|---------|----------------|-----------|------------|----------|
| FGH60N60SFDTU-F085 | FGH60N60SFD | TO-247 | Tube | N/A | N/A | 30 |

Electrical Characteristics of the IGBT

$T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|----------------------------------|--|--|------|------|-----------|---------------------------|
| Off Characteristics | | | | | | |
| BV_{CES} | Collector to Emitter Breakdown Voltage | $V_{GE} = 0 \text{ V}, I_C = 250 \mu\text{A}$ | 600 | - | - | V |
| $\Delta BV_{CES} / \Delta T_J$ | Temperature Coefficient of Breakdown Voltage | $V_{GE} = 0 \text{ V}, I_C = 250 \mu\text{A}$ | - | 0.4 | - | $\text{V}/^\circ\text{C}$ |
| I_{CES} | Collector Cut-Off Current | $V_{CE} = V_{CES}, V_{GE} = 0 \text{ V}$ | - | - | 250 | μA |
| I_{GES} | G-E Leakage Current | $V_{GE} = V_{GES}, V_{CE} = 0 \text{ V}$ | - | - | ± 400 | nA |
| On Characteristics | | | | | | |
| $V_{GE(\text{th})}$ | G-E Threshold Voltage | $I_C = 250 \mu\text{A}, V_{CE} = V_{GE}$ | 4.0 | 5.1 | 6.6 | V |
| $V_{CE(\text{sat})}$ | Collector to Emitter Saturation Voltage | $I_C = 60 \text{ A}, V_{GE} = 15 \text{ V}$ | - | 2.2 | 2.9 | V |
| | | $I_C = 60 \text{ A}, V_{GE} = 15 \text{ V}, T_C = 125^\circ\text{C}$ | - | 2.4 | - | V |
| Dynamic Characteristics | | | | | | |
| C_{ies} | Input Capacitance | $V_{CE} = 30 \text{ V}, V_{GE} = 0 \text{ V}, f = 1 \text{ MHz}$ | - | 2940 | - | pF |
| C_{oes} | Output Capacitance | | - | 310 | - | pF |
| C_{res} | Reverse Transfer Capacitance | | - | 100 | - | pF |
| Switching Characteristics | | | | | | |
| $t_{d(on)}$ | Turn-On Delay Time | $V_{CC} = 400 \text{ V}, I_C = 60 \text{ A}, R_G = 5 \Omega, V_{GE} = 15 \text{ V}, \text{Inductive Load, } T_C = 25^\circ\text{C}$ | - | 26 | - | ns |
| t_r | Rise Time | | - | 54 | - | ns |
| $t_{d(off)}$ | Turn-Off Delay Time | | - | 134 | - | ns |
| t_f | Fall Time | | - | 18 | 62 | ns |
| E_{on} | Turn-On Switching Loss | | - | 1.97 | - | mJ |
| E_{off} | Turn-Off Switching Loss | | - | 0.57 | - | mJ |
| E_{ts} | Total Switching Loss | | - | 2.54 | - | mJ |
| $t_{d(on)}$ | Turn-On Delay Time | $V_{CC} = 400 \text{ V}, I_C = 60 \text{ A}, R_G = 5 \Omega, V_{GE} = 15 \text{ V}, \text{Inductive Load, } T_C = 125^\circ\text{C}$ | - | 26 | - | ns |
| t_r | Rise Time | | - | 50 | - | ns |
| $t_{d(off)}$ | Turn-Off Delay Time | | - | 142 | - | ns |
| t_f | Fall Time | | - | 24 | - | ns |
| E_{on} | Turn-On Switching Loss | | - | 2.5 | - | mJ |
| E_{off} | Turn-Off Switching Loss | | - | 0.8 | - | mJ |
| E_{ts} | Total Switching Loss | | - | 3.2 | - | mJ |
| Q_g | Total Gate Charge | $V_{CE} = 400 \text{ V}, I_C = 60 \text{ A}, V_{GE} = 15 \text{ V}$ | - | 188 | - | nC |
| Q_{ge} | Gate to Emitter Charge | | - | 21 | - | nC |
| Q_{gc} | Gate to Collector Charge | | - | 98 | - | nC |

Electrical Characteristics of the Diode $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | | Min. | Typ. | Max | Unit |
|----------|-------------------------------|---|---------------------------|------|------|-----|------|
| V_{FM} | Diode Forward Voltage | $I_F = 30 \text{ A}$ | $T_C = 25^\circ\text{C}$ | - | 1.9 | 2.6 | V |
| | | | $T_C = 125^\circ\text{C}$ | - | 1.7 | - | |
| t_{rr} | Diode Reverse Recovery Time | $I_F = 30 \text{ A}, di_F/dt = 200 \text{ A}/\mu\text{s}$ | $T_C = 25^\circ\text{C}$ | - | 55 | - | ns |
| | | | $T_C = 125^\circ\text{C}$ | - | 204 | - | |
| | | | $T_C = 25^\circ\text{C}$ | - | 125 | - | nC |
| | | | $T_C = 125^\circ\text{C}$ | - | 895 | - | |
| Q_{rr} | Diode Reverse Recovery Charge | | | | | | |

Typical Performance Characteristics

Figure 1. Typical Output Characteristics




Figure 3. Typical Saturation Voltage Characteristics




Figure 5. Saturation Voltage vs. Case Temperature at Variant Current Level




Figure 2. Typical Output Characteristics




Figure 4. Transfer Characteristics





Figure 6. Saturation Voltage vs. V_{GE}



Typical Performance Characteristics

Figure 7. Saturation Voltage vs. V_{GE}




Figure 8. Saturation Voltage vs. V_{GE}




Figure 9. Capacitance Characteristics




Figure 10. Gate charge Characteristics




Figure 11. SOA Characteristics





Figure 12. Turn off Switching SOA Characteristics



Typical Performance Characteristics

Figure 13. Turn-on Characteristics vs. Gate Resistance




Figure 15. Turn-on Characteristics vs. Collector Current




Figure 17. Switching Loss vs Gate Resistance




Figure 14. Turn-off Characteristics vs. Gate Resistance




Figure 16. Turn-off Characteristics vs. Collector Current





Figure 18. Switching Loss vs Collector Current



Typical Performance Characteristics

Figure 19. Forward Characteristics




Figure 20. Reverse Current




Figure 21. Stored Charge




Figure 22. Reverse Recovery Time






Figure 23. Transient Thermal Impedance of IGBT



Mechanical Dimensions



NOTES: UNLESS OTHERWISE SPECIFIED.

- A. PACKAGE REFERENCE: JEDEC TO-247,
ISSUE E, VARIATION AB, DATED JUNE, 2004.
- B. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD
FLASH, AND TIE BAR EXTRUSIONS.
- C. ALL DIMENSIONS ARE IN MILLIMETERS.
- D. DRAWING CONFORMS TO ASME Y14.5 - 1994

DOES NOT COMPLY JEDEC STANDARD VALUE

NOTCH MAY BE SQUARE

- G. DRAWING FILENAME: MKT-TO247A03_REV03

Figure 24. TO-247 3L - TO-247, MOLDED, 3 LEAD, JEDEC VARIATION AB

Package drawings are provided as a service to customers considering ON Semiconductor components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a ON Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of ON Semiconductor's worldwide terms and conditions, specifically the warranty therein, which covers ON Semiconductor products.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local
Sales Representative