



Bill of Materials for the LV8713TGEVB Evaluation Board

Designator	Quantity	Description	Value	Tolerance	Footprint	Manufacturer	Manufacturer Part Number	Substitution Allowed	Lead Free
C1	1	REG5 stabilization Capacitor	0.1μF, 100V	±10%	1608	Murata	GRM188R72A104KA35*	Yes	Yes
C2	1	Capacitor to set chopping frequency	180pF, 50V	±5%	1608	Murata	GRM1882C1H181JA01*	Yes	Yes
C3	1	VCC Bypass Capacitor	0.1μF, 100V	±10%	1608	Murata	GRM188R72A104KA35*	Yes	Yes
C4	1	VM Bypass Capacitor	10μF, 50V	±20%	F2.0-5	SUN Electronic	50ME10HC	Yes	Yes
R1	1	Pull-up Resistor for terminal MONI	47kΩ, 1/10W	±5%	0603	KOA	RK73B1JT**473J	Yes	Yes
R2	1	Channel 1 output current detective	0.47Ω, 1W	±5%	6432 (2512)	ROHM	MCR100JZHJLR47	Yes	Yes
R3	1	Channel 2 output current detective	0.47Ω, 1W	±5%	6432 (2512)	ROHM	MCR100JZHJLR47	Yes	Yes
IC1	1	Motor Driver	-	-	TSSOP24 (225mm)	ON Semiconductor	LV8713T	No	Yes
SW1-SW8	8	Switch	-	-	-	MIYAMA	MS-621C-A01	Yes	Yes
TP1-TP21	21	Test Point	-	-	-	MAC8	ST-1-3	Yes	Yes